

Features and Benefits

Polycom[®] HDX 6000™



Audio	Benefits
Polycom 22 kHz StereoSurround™ with 2 channels of 22 kHz crystal-clear audio	 Hear everyone clearly and naturally Superb clarity to hear the subtleties of every word, conversation and speakers Hear all participants, even when multiple people are
Audio Error Concealment • Eliminates audio drop-outs on noisy networks	 talking Smooth and consistent verbal communications free from interruptions Automatic correction of audio quality whenever needed
Multiple Audio Inputs for aux audio or DVD	Allows far end to hear audio from PC or other multimedia device
Video	Benefits
 Incredible video resolutions at all bandwidths DVD quality video (256 Kbps – 768kbps) High Definition 720p30 Video from 832kbps – 2 Mbps 	Natural motion and superb video at any data rate
Polycom EagleEye™ HDX Camera • 1/3 2 MP CMOS Imager • 72 deg FOV at min zoom • Capture at 1280x720 resolution • 12x Optical Zoom • 16:9, 720p60 video capture • Sharp, quick focus	 Wide screen captures full room for maximum participation Natural interaction between all meeting participants Sharp, quick focus enables a highly productive meeting and eliminates technology issues
Lost Packet Recovery (LPR)	 Smooth uninterrupted video conferences, even on congested networks Faster and more productive meetings Seamless and automatic activation without IT intervention
 Dual Monitor Emulation View near and far video windows at the same time in native aspect ratio 	 High quality communications for near end and far end participants Optimal use of display investments
HDMI support	Single cable support for both video and audio allows for simple, clean setup
Additional HD Video input	Share data from a computer or other video source



Content Sharing	Benefits
Standards based H.239 ensures fully interoperability People+Content IP allows users to share data through network without a direct connection to HDX 6000.	 Improved meeting quality with simultaneous speaker and content views Uninterrupted conferences with intuitive on-touch content sharing
Adjustable Bandwidth for Content	 Sustained meeting quality across a wide range of content during a video call Users have best overall experience with no intervention
 System will automatically adjust bandwidth allocation when sharing content based upon content being shown 	

Platform Versatility	Benefits
Secure FTP, Telnet and Web	 Polycom video systems are the most secure video conferencing solutions in the industry All access to the HDX system can be secured including accessing the HDX system via web-browser as well as secure telnet and ftp access via SSH for secure system administration and application connectivity
Advanced Encryption Standard (AES)	 Communications are confidential and secure Authentication by the National Institutes of Standards means it's credible Built-in, no extra hardware required
H.460 NAT/Firewall Traversal	 Standards compliance for traversing NATs and Firewalls Session border controller (V2IU) is only needed at the central location and all VSX systems with H.460 can communicate through the single V2IU Uses H.460.18 for signaling traversal and call establishment and H.460.19 for media traversal
IP (H.323 or SIP)	 IP and SIP standard Choose the right option for your specific network connection Supports UPnP and NAT for automatic setup of conferences conducted through firewalls Wide range of IP QoS services to insure call quality and integrity



Interoperability	Benefits
Part of Polycom's Unified Collaborative Communications	 Remote management through Polycom CMA 4000[™] or 5000 RMX Click & View[™] offers a variety of layout templates for multipoint call right from the system's handheld remote Play, stop, record, rewind and fast forward video recordings with the RSS 2000 using the HDX remote control Expand the audience over audio and video with an RMX[™] bridge Schedule, invite participants and manage conferences easily with Polycom Conference Suite Video recording, streaming and archiving with the Polycom RSS 2000[™]
Standards-based	 Solid, reliable platform Qualified by independent test labs Interoperates with other standards-based systems in the industry Easy to install even in a multi-vendor environment

Polycom Moscow zakaz@polycom-moscow.ru
T+7 495 924-25-25
www.polycom-moscow.ru

